

Parto Khazen Co.

No. 15, 1st. Alley, Gandi Ave., 15176 Tehran, Iran Tel: (+98 21) 88882956-8

Fax: (+98 21) 88882959

Certificate Of Compliance 12.5 KVAR /400 V /50HZ

Product: Power Factor Correction Capacitor (PFC)

Model: PAC 3 Phase (△ Connection)

Technical Specifications:

- Rated Power: 12.5 KVar - Protection: Overpressure Disconnector

- Rated Voltage: 400 Vac - Terminal Type: ST (Modular Polyamide)

- Rated Frequency 50 Hz - Filling Material: Non PCB – N2 Gas

- Capacitance: $3 \times 82.9 \, \mu F_{-5\%}^{+5\%}$ - Fixing: M12

- Operating Temp.: -25 °C/+55 °C - Max. Permissible Torque on Stud: ---

- Expected Life: 100,000 hrs - Mounting: Vertical & Horizontal

- Discharge Resistor: $270 \text{ k}\Omega$, 2 W, Δ - Can: Aluminum

- Discharge Time: 60 Sec - Lid: Aluminum

- Max. Permissible Voltage: 1.1 Un - Dimension $(D \times H)$: 70×280 mm

- Max. Permissible Current: 1.3 In

Routine Tests:

- Voltage Test Between Terminals: 860 Vac, 2 Sec. (Type Test: 860 Vac, 10 Sec.)
- Voltage Test Between Case and Terminals: 3.6 KVac, 2 Sec. (Type Test: 3 KVac, 60 Sec.)
- Sealing Test: 85 °C, 2 hrs.
- Test Of The Discharge Device
- Capacitance Measurement
- Measurement of the Tangent of the Loss Angle (tang δ)
- Lightning Impulse Voltage Test: (Type Test: 8 KV)

It's hereby Certified these Products are tested and inspected according to International Standard IEC 60831 (2014) and all your expectations have been met therein.

F8-62-25/0

Authorized Sign.
Quality Control